

# WAC LIGHTING

Responsible Lighting®

## Dimming Compatibility

ID E2011061VO

**Product Family:** Jasmine  
**Sku Tested:** WS-77127  
**Related Models** WS-77137

**Test Voltage:** 120V  
**Control Type:** ELV/TRIAC

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	0.7%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	46.0%	Flicker below 46%
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	96.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	22.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	32.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	12.0%	Not Recommended
Cooper	AL Series	AAL06	120	N/A	Flashing at high dimming level
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	13.0%	
Lutron	Diva	DVELV-300P	120	7.0%	
Lutron	Maestro	MAELV-600	120	2.0%	
Lutron	Skylark	SELV-300P	120	7.0%	
Leviton	Illumatech	IPE04-1LZ	120	45.0%	Flicker below 45%
Lutron	Maestro	RRD-6NA	120	2.0%	
Leviton	SureSlide	6615-POW	120	39.0%	Flicker below 39%
Leviton	Decora	DSE06-10Z	120	5.0%	
Lutron	Caseta	PD-5NE	120	9.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Lutron	Homeworks	HQRD-6NA	120	2.0%	
Leviton	Renoir II	AWSMT-EBW	120	0.7%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	2.0%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MACL-153M-WH	120	4.0%	
Lutron	Diva	DVCL-153P	120	40.0%	Flicker below 40%
Legrand	Adorne Paddle	ADPD453LW2	120	21.0%	
Lutron	Ariadni	AYCL-153PH	120	3.0%	
Lutron	Skylark	SCL-153P-WH	120	68.0%	Flashing at high dimming level
Lutron	Maestro	MA-600-WH	120	N/A	Dimmer not responsive
Leviton	SureSlide	6674-POW	120	6.0%	
Lutron	Caseta	PD-6WCL	120	19.0%	Flicker below 19%
Legrand	Harmony	HCL453PW	120	3.0%	Flicker below 3%
Legrand	Radiant	RHCL453PW	120	4.0%	Flashing at low dimming level

# WAC LIGHTING

Responsible Lighting®

## Dimming Compatibility

ID E2011063V0

**Product Family:** Jasmine  
**Sku Tested:** WS-77137  
**Related Models** WS-77127

**Test Voltage:** 120V  
**Control Type:** ELV/TRIAC

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	0.9%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	72.0%	Flashing at high dimming level
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	71.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	11.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	16.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	13.0%	Not Recommended
Cooper	AL Series	AAL06	120	8.0%	Flicker below 8%
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	11.0%	
Lutron	Diva	DVELV-300P	120	6.0%	
Lutron	Maestro	MAELV-600	120	2.0%	
Lutron	Skylark	SELV-300P	120	6.0%	
Leviton	Illumatech	IPE04-1LZ	120	35.0%	Flicker below 35%
Lutron	Maestro	RRD-6NA	120	2.0%	
Leviton	SureSlide	6615-POW	120	46.0%	Flicker below 46%
Leviton	Decora	DSE06-10Z	120	46.0%	Flicker below 46%
Lutron	Caseta	PD-5NE	120	69.0%	Flashing at high dimming level
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Lutron	Homeworks	HQRD-6NA	120	2.0%	
Leviton	Renoir II	AWSMT-EBW	120	0.8%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	1.0%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MACL-153M-WH	120	4.0%	
Lutron	Diva	DVCL-153P	120	73.0%	Flashing at high dimming level
Legrand	Adorne Paddle	ADPD453LW2	120	20.0%	
Lutron	Ariadni	AYCL-153PH	120	2.0%	
Lutron	Skylark	SCL-153P-WH	120	40.0%	Flicker below 40%
Lutron	Maestro	MA-600-WH	120	N/A	Dimmer not responsive
Leviton	SureSlide	6674-POW	120	5.0%	
Lutron	Caseta	PD-6WCL	120	13.0%	Flicker below 13%
Legrand	Harmony	HCL453PW	120	1.0%	
Legrand	Radiant	RHCL453PW	120	18.0%	Flicker below 18%

# WAC LIGHTING

Responsible Lighting®

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or [sales@wacighting.com](mailto:sales@wacighting.com).