# OCULUX - model: 7030

# H/L/J Track Luminaire

# WAC LIGHTING


# Responsible Lighting®



Fixture Type:

Catalog Number:

Project:
Location:



#### PRODUCT DESCRIPTION

Ideal for retail and higher-mounted residential spaces, the OCULUX 7030 balances the output of a high efficiency LED with the flexibility of three beam spreads and glare control compatibility. Oculux is available in H, J/J2, and L track configurations. Order according to track layout specifications.

### **FEATURES**

#### • 3 beam angle options included:

55° beam film pre-installed, interchangeable 38° film supplied, remove film for 16° spot beam

- Integral driver and high output COB LED
- Outperforms halogen 100W PAR38
- 350° horizontal and 90° vertical aiming
- Accommodates one lens OR one glare control accessory
- 5 year warranty

## **SPECIFICATIONS**

**Construction:** Die-cast aluminum with baffled front cover for glare control

Input Power: 32W at 120VAC, 50/60Hz (PF: 0.98)

**THD(A):** < 15% Total Harmonic Distortion (Current)

**Light Source:** High output 3 Step Mac Adam, Ellipse COB, 90+ CRI

Rated Life of 50,000 hours at L70

**Dimming:** ELV or Forward Phase: 100 - 10%

Reference dimming report for compatibility.

**Standards:** ETL & cETL Dry Location Listed, Title 24 JA8-2016 Compliant

Finish: Electrostatically powder coated Black, Dark Bronze, and White

**Electroplated Brushed Nickel** 

Operating

**Temperature:**  $32^{\circ}F$  to  $104^{\circ}F$  ( $0^{\circ}C$  to  $40^{\circ}C$ )

#### REPLACEMENT OPTICS

38°	Narrow Flood Film	FILM-20-N
55°	Flood Film	FILM-20-F

System	Model	Beam	Max Lumens	Max CBCP	Color	Temp	CRI	T24	Energy Star	Finis	h	
H HTrack L LTrack J J/J2 Track	7030	16° 38° 55°	2025 1855 1850	11641 2918 1641	930	3000K	90	Yes	Yes	BK BN DB WT	Black Brushed Nickel Dark Bronze White	

-7030-930-

Example: H-7030-930-BN

Accommodates one lens accessory OR one glare control accessory

#### **COLOR LENS**

Amber	LENS-20-AMB
Blue	LENS-20-BLU
Green	LENS-20-GRN
Red	LENS-20-RED

## **FLAT LENS**

Frosted LENS-20-FR Spread LENS-20-SPR Beam Elongating LENS-20-BEL

## **GLARE CONTROL**

LENS-20P-CRL-BK
LENS-20P-CRL-BN
LENS-20P-CRL-WT
LENS-20-SNOOT-BK
LENS-20-SNOOT-BN
LENS-20-SNOOT-WT
LENS-20-HCL

**waclighting.com** Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760